

FC-6 fibre cleavers

Rugged bench top tools for fibre preparation



Security label shows genuine product

- black changes to silver and silver to black when tool is rotated 90°
- 'OK OK OK' visible when viewed through a polariser

Offcut collector on -C models

- high capacity for offcuts
- collector drawer slides out for safe disposal of fibre sharps



Auto-rotating blade on 6R models

- no routine adjustment needed
- always set to correct height
- great cleaves, always

Stable base for reliable operation

	FC-6S	FC-6S-C	FC-6RS	FC-6RS-C	FC-6RM-C
FIBRE TYPES	125um SMF, MMF, NZDSF, BIF and others				
USE FIBRE HOLDER	Yes				
CLEAVE LENGTH 250um	5 to 20mm with single fibre adaptor, 10mm with fibre holders				
CLEAVE LENGTH 900um	10 to 20mm with single fibre adaptor, 10mm with fibre holders				
HARD CARRYING CASE	Included				
FIBRE NUMBER	1				1 to 12
FIBRE RIBBON	Not recommended for ribbon cleaving				Yes
SINGLE FIBRE ADAPTOR	Included with the cleaver				Option
DIMENSIONS (mm)	63x76x63	100x81x63	63x77x63	100x81x63	100x81x63
WEIGHT	Approx 380g	Approx 420g	Approx 380g	Approx 420g	Approx 420g
OFFCUT COLLECTOR	No	Yes	No	Yes	
AUTO ROTATING BLADE	No	No	Yes	Yes	
FIELD REPLACEABLE BLADE	Yes, use FCP-20BL			Yes, use FCP-20BL(7R)	
BLADE LIFE	54000 cleaves			60000 cleaves	

Sumitomo Electric reserves the right to alter product specifications without notice E&OE

Sumitomo Electric Europe Ltd www.sumielectric.com seel@sumielectric.com

Document part number TZA013DO0001-10 Document release date 2020-04-20

© Sumitomo Electric Europe Ltd