

FTTH XPON ONT Wireless 4LAN + Voip

ST-XP114



Key Features :



2 telephone ports
(POTS-RJ11)



Detecting
Rogue ONU



WiFi
IEEE802.11b/g/n



4 Gigabit Ethernet
ports (LAN)

Product Overview :

ST-XP114 is a GPON ONT client terminal used in FTTH networks. It has 2 phone sockets (POTS-RJ11), 4 Gigabit Ethernet ports, USB port and one GPON class B+ port. The device can also use wireless transmission using two antennas with 2dBi gain each. When using Wi-Fi it is possible to create multiple SSIDs. The maximum power consumption of ST-XP114 is only 15.5W.

Key Features :

- port GPON (class B+)
- 4 Gigabit Ethernet ports (LAN)
- 2 telephone ports (POTS-RJ11)
- Wi-Fi in IEEE802.11b/g/n standard
- two external antennas with profit 2 dBi each
- USB 2.0 port
- functions Layer 3 and QoS-energy savings

Product specifications		
Interfaces Parameter	LAN ports	4x 10/100/1000BaseTX (Rj45)
	PON standard	GPON
	Wireless network standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n,
	USB port	1x USB
	VoIP ports	2x POTS
	Dimensions	176x138.5x28 mm (without antenna)
	Weight	About 500 g
	Permissible operating temperature	0 to 40 degrees C
	Permissible air humidity	5%-95% RH non-condensing
	LEDs	POWER / PON / FATE / LAN / TEL / USB / WLAN / WPS
	Set composition	The device 12 V, 2 A power supply Ethernet cable
	WLAN	IEEE 802.11 b/g/n 2x2 MIMO Antennas with 2 dBi gain WMM Many SSIDs WPS
Hardware Parameter	PON	1 port Class B+ Sensitive reception:-27 dBm Wavelength: US 1310nm, Ds1490nm WBF Flexible mapping between the GEM and TCONT ports G.984.3 Bilateral FEC SR-DBA and NSR-DBA
	Ethernet	4 Gigabit ports 1:1 VLAN, N:1 VLAN or VLAN transparent transmission QinQ VLAN MAC address learning

Product specifications		
Hardware Parameter	POTS	2 ports Maximum REN: 4 G.711A/u, G.729a/b and G.722 T.30 / T.38 / G.711 fax DTMF Emergency calls (via SIP protocol)
	Ports	2 POTS 4 Gigabit ports of Ethernet USB GPON
Function data	Power input	100- 240 V AC, 50- 60 Hz
	System power supply	11- 14 V DC, 2 A
	Static power consumption	5 W
	Maximum power consumption	15,5 W



SUMICO

Tarvij Sanat Sumi Parsian Co. LTD
No.1, 4th Narges Alley, Azadi Bolv. Shams-Abad Industry Park,
Tehran-Qom Highway, Hasan Abad Fashafooye, Tehran, Iran
Tel: +98 21 43614000 Fax:+98 21 43614300
E-Mail:info@sumico.ir PC: 1834179535

توجه :

sumico حق تغییر مشخصات را بدون اطلاع قبلی دارد. اگر چه اطلاعات جمع آوری شده در این دیتاشیت با دقت صورت گرفته، ولی نباید تضمینی برای محصول نهایی گردد. sumico فقط در رابطه با مشخصاتی که عیناً در فاکتور فروش و هنگام عقد قرارداد قید میشود، مسئولیت دارد. هرگونه استفاده و کپی برداری از منابع و محصولات، تنها با اجازه نامه کتبی از sumico مجاز میباشد و هرگونه استفاده غیر، پیگرد قانونی دارد.

Specifications are subject to change without notice. Copyright ©2023 SUMICO CO.,LTD. All rights reserved.

Soltek is the trademark of Tarvij Sanat Sumi Parsian Co.

All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.