

FTTH XPON ONT 4LAN+ VOIP Wireless 1300 AC

ST-XP130



Product Overview :

ST-XP130 is an ONT terminal designed for GPON networks. It is equipped with 4 gigabit Ethernet ports, 2 USB ports and 1 RJ11 (POTS) phone port. The device enables wireless network transmission thanks to IEEE802.11ac standard and 3 x 3 MIMO technology. It works simultaneously at two frequencies, 450 Mbit/s at 2.4 GHz and 1300 Mbit/s at 5 GHz. The ST-XP130 terminal is an ideal solution for home (HGU- Home Gateway Unit) for FTTH scenarios. To easily create an intelligent home network, the gateway supports Layer 3 functionality. It provides users with Triple-play service (Internet, VoIP telephony, IPTV) . The offered product is equipped with a GPON port of SC/UPC class B+. The device uses a tower type standing casing. The set includes a 12 V 2 A power supply.

Key Features :

- 4 Gigabit Ethernet ports
- 1 RJ11 telephone port (POTS)
- 2 USB ports
- Dual band Wi-Fi radio, 2.4 GHz and 5 GHz AC
- 3 x 3 MIMO, up to 450 Mb/s in the 2.4 GHz band and up to 1300 Mb/s in the 5 GHz band
- Built-in antennas with 2 dBi gain

Product specifications		
Interfaces Parameter	GPON	Class B+ Sensitive reception: 27 dBm Wavelength: US 1310 nm, DS 1490 nm WBF Flexible mapping between the GEM and TCONT ports
	Ethernet port	4 ports 10/100/1000 BASE-T (Rj45)
	POTS Port	Maximum REN: 4 G.711A/μ, G.729a/b and G.722 Encoding/decoding T.30/T.38/G.711 fax mode DTMF
	USB port	2 USB 2.0 ports Possibility to create a network drive based on FTP
	WLAN	IEEE 802.11 b/g/n (2.4G) IEEE 802.11 a/n/ac (5G) 3 × 3 MIMO Antennas with 2 dBi gain WMM Multiple SSIDs WPS 450 Mbit/s (2.4 G); 1300 Mbit/s (5 G)
	LEDs	POWER/PON/LOS/TEL/LAN/WLAN/WPS/USB
Hardware Parameter	Dimensions	265 mm x 176 mm x 82 mm
	Weight	1500 g
	Permissible operating temperature	0°C to 40°C
	Permissible air humidity	5%-95% RH, non-condensing
	Power input	100-240 V AC, 50/60 Hz
	System power supply	11-14 V DC, 2 A
	Static power consumption	8 W
	Maximum power consumption	20.5 W

Product specifications		
Function data	Intelligent connection	Intelligent Wi-Fi coverage Automatic negotiation SIP/ H.248 All port services Parental control L2 / L3 transmission (IPv4): 1G uplink, 2G downlink
	Intelligent handling	Intelligent Wi-Fi sharing Authentication of portal 802.1 xSharing based on SoftGRE Linking one account to two POTS ports



SUMICO

Tarvij Sanat Sumi Parsian Co. LTD
No.1, 4th Narges Alley, Azadi Bolv. Shams-Abad Industry Park,
Tehran-Qom Highway, Hasan Abad Fashafooye, Tehran, Iran
Tel: +98 21 43614000 Fax:+98 21 43614300
E-Mail:info@sumico.ir PC: 1834179535

توجه :

sumico حق تغییر مشخصات را بدون اطلاع قبلی دارد. اگر چه اطلاعات جمع آوری شده در این دیتاشیت با دقت صورت گرفته، ولی نباید تضمینی برای محصول نهایی گردد. sumico فقط در رابطه با مشخصاتی که عیناً در فاکتور فروش و هنگام عقد قرارداد قید میشود، مسئولیت دارد. هرگونه استفاده و کپی برداری از منابع و محصولات، تنها با اجازه نامه کتبی از sumico مجاز میباشد و هرگونه استفاده غیر، پیگرد قانونی دارد.

Specifications are subject to change without notice. Copyright ©2023 SUMICO CO.,LTD. All rights reserved.

Solttek is the trademark of Tarvij Sanat Sumi Parsian Co.

All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.